```
                    Z A K L A D N I     D E F I N I C E
                    -----------------------------------
--Co je to arrow
class Arrow a where
    --povinne
    arr   :: (b->c) -> a b c
    (>>>) :: a b c -> a c d -> a b d
    -- zatim to nestaci, protoze nemam jak zkombinovat parametry
    -- add :: Arrow a => (a b Int) -> (a b Int) ->(a b Int)
    first :: a b c -> a (b,d) (c,d)

    --nepovinne, lze definovat z povinnych
    second :: a b c -> a (d,b) (d,c)
    second f = arr swap >>> first f >>> arr swap
     where
      swap (x,y) = (y,x)

    (***) :: a b1 c1 -> a b2 c2 -> a (b1,b2) (c1,c2)
    f *** g = first f >>> second g

    (&&&) :: a b c1 -> a b c2 -> a b (c1,c2)
    f &&& g = arr (\b->(b,b)) >> (f *** g)

--Monady jsou Arrow
newtype Kleisli m a b = K (a -> mb)
instance Monad m => Arrow (Kleisli m) where
    arr f = K (\b -> return (f b))                          -- K (return $ f id)
    K f >>> K g = K (\b -> f b >>= g)                       -- K (f id >>= g)
    first (K f) = K (\(b,d) -> f b >>= \c -> return (c,d))

--Dalsi rozsireni Arrow
class Arrow a => ArrowZero a where zeroArrow :: a b c
class Arrow a => ArrowPlus a where (+++) :: a b c -> a b c -> a b c

--Choice
class Arrow a => ArrowChoice a where
    --povinne
    left :: a b c -> a (Either b d) (Either c d)

    --nepovinne
    right f = arr mirror >>> left f >>> arr mirror
     where
      mirror (Left x) = Right x
      mirror (Right x) = Left x

    f <+> g = left f >>> right g

    f ||| g = (f <+> g) >>> arr untag
     where
      untag (Left x) = x
      untag (Right x) = x

instance Monad m => ArrowChoice (Kleisli m) where
    left (K f) = K (\x -> case x of Left b -> f b >>= \c -> return (Left c)
                                    Right d -> return (Right d))
--Apply
class Arrow a => ArrowApply a where
    app :: a (a b c , b) c

instance Monad m => ArrowApply (Kleisli m) where
    app = K( \ (K f, x) -> f x)

--ArrowApply uz je Monada
newtype ArrowApply a => ArrowMonad a b = M (a Void b)
instance ArrowApply a => Monad (ArrowMonad a) where
    return x = M (arr (\z -> x))
    M m >>= f = M ( m >>>
                    arr (\x -> let M h = f x in (h, ())) >>>
                    app )
```

S T A T E A R R O W

```
prod::(a1->b1)->(a2->b2)->(a1,a2)->(b1,b2)
(f `prod` g) (a1,a1) = (f a1, g a2)

newtype State s a b = ST ((s, a) -> (s, b))
instance Arrow (State s) where
    arr f = ST (id `prod` f)
    ST f >>> ST g = ST (g . f)
    first (ST s) = ST (assoc . (f`prod`id) . unassoc) where
       assoc   ((a,b),c) = (a,(b,c))
       unassoc (a,(b,c)) = ((a,b),c)

fetch::State s () s
fetch = ST (\(s,_) -> (s,s))
store::State s s ()
store = ST (\(_,s')->(s',()))

nextNum::State Int () Int
nextNum = fetch >>> arr ((+1)`prod`id) >> first store >>> arr snd
nextNum = proc () -> do n <- fetch -< ()
                        store -< (n+1)
                        returnA -< n
```

I N T E R P R E T E R V M O N A D A C H A A R R O W

```
--1) promenne a cisla
data Exp = Var String | Add Exp Exp
data Val = Cislo Int
type Env = [(String, Val)]

--M O N A D Y                                  A R R O W
eval::Exp -> Env -> M Val                     eval::Exp -> A Env Val
eval (Var s) env = return (lookup s env)      eval (Var s) = arr (lookup s)
eval (Add e1 e2) env =                        eval (Add e1 e2) =
  liftM2 add (eval e1 env) (eval e2 env)        liftA2 add (eval e1) (eval e2)
   where                                      --((eval e1) &&& (eval e2)) >>>
    add (Cislo a) (Cislo b) = Cislo (a+b)     --arr (\(a,b) -> a `add` b)

--2) podminky
data Exp = ... | If Exp Exp Exp
data Val = ... | Bl Bool

--M O N A D Y                          A R R O W
eval (If e1 e2 e3) env = do           eval (If e1 e2 e3)=(eval e1 &&& arr id)>>>
  podm <- eval e1 env     arr(\(Bl b,env)->if b then Left env else Right env)>>>
  if b then eval e2 env                                  (eval e2 ||| eval e3)
  else eval e3 env

--3) lambda-kalkulus
data Exp = ...|Lam String Exp | App Exp Exp
data Val = ...|Fun (Val -> M Val) -- monady
data Val = ...|Fun (A Val Val) -- arrow

--M O N A D Y                                 A R R O W
eval (Lam x e) env =                          eval (Lam x e) = arr (\env ->
  return (Fun (\v -> eval e((x,v) : env))       Fun(arr(\v->(x,v):env)>>>eval e))
eval (App e1 e2) env=eval e1 env>>=           eval (App e1 e2) =
  \Fun f -> eval e2 env >>= \v -> f v    ((eval e1>>>arr(\Fun f->f)) &&& eval e2)
                                                                  >>> app
--DO NOTACE
eval (Add e1 e2) env = do                     eval (Add e1 e2) = proc env -> do
  Cislo a1 <- eval e1 env                       Cislo a1 <- eval e1 -< env
  Cislo a2 <- eval e2 env                       Cislo a2 <- eval e2 -< env
  return $ Cislo (a1 + a2)                      returnA -< Cislo (a1 + a2)
eval (If e1 e2 e3) env = do                   eval (If e1 e2 e3) = proc env -> do
  podm <- eval e1 env                           podm <- eval e1 -< env
  if b then eval e2 env else eval e3 env        (eval e2 ||| eval e3) -<
                                              if podm then Left env else Right env
```

```
                    S T R E A M    P R O C E S O R Y
                    ---------------------------
data SP a b = Put b (SP a b) | Get (a -> SP a b)

instance Arrow SP where
    arr f = Get (\x->Put (f x) (arr f))

    sp1       >>> Put c sp2 = Put c (sp1>>>sp2)
    Put b sp1 >>> Get f     = sp1 >>> f b
    Get f1    >>> sp2       = Get (\x -> f1 x >>> sp2)

    first f = bypass [] f where
      bypass ds (Get f) = Get (\(b,d)->bypass (ds++[d]) (f b))
      bypass (d:ds) (Put c sp) = Put (c,d) (bypass ds sp)
      bypass [] (Put c sp) = Get (\(b,d)->Put (c,d) (bypass [] sp))

fibs::SP Int Int
fibs = Put 0 fibs' where fibs' = Put 1 (liftA2 (+) fibs fibs')

instance ArrowZero SP where zeroArrow = Get (\x->zeroArrow)

instance ArrowPlus SP where Put b sp1 <+> sp2 = Put b (sp1<+>sp2)
                            sp1 <+> Put b sp2 = Put b (sp1<+>sp2)
                            Get f1 <+> Get f2 = Get (\a->f1 a<+>f2 a)

instance ArrowChoice SP where left (Put c sp)=Put (Left c) (left sp)
                              left (Get f) = Get (\z->case z of
                                     Left a->left (f a)
                                     Right a->Put (Right a) (left (Get f)))

          P A R S E R    S E    S T A T I C K O U    I N F O R M A C I
          ---------------------------------------------------------
data StaticParser      = SP Bool [Char]
data DynamisParser a b = DP ((a,String)->(b,String))
data Parser        a b = P StaticParser (DynamicParser a b)

instance Arrow Parser where
    arr f = P (SP True []) (DP (\(b,s)->(f b,s)))

    P (SP e1 s1) (DP p1) >>> P (SP e2 s2) (DP p2) =
        P (SP (e1 && e2) (s1 `union` if e1 then s2 else []))
          (DP (p2 . p1))
    first (P sp (DP p)) = P sp (\((b,d),s)->let (c,s')=p (b,s) in ((c,d),s')

instance ArrowZero Parser where zeroArrow = P (SP False []) (DP undefined)
instance ArrowPlus Parser where P (SP e1 s1) (DP p1) <+> P (SP e2 s2) (DP p2) =
   P (SP (e1 || e2) (s1 ++ s2)) (DP (\(b,s)->case s of
                                  []  -> if e1 then p1 [] else p2 []
                                  c:cs-> if c`elem`s1 then p1 s else
                                         if c`elem`s2 then p2 s else
                                         if e1 then p1 s else p2 s))
--neni ArrowChoice ani ArrowApply

              N E D E T E R M I N I S T I C K E    V Y P O C T Y
              ------------------------------------------------
newtype NonDet a b = ND (a->[b])

instance Arrow NonDet where
    arr f = ND (\a->[f a])
    ND f >>> ND g = ND (\a->[c | b<-f a,c<-g b])
    first (ND f) = ND (\(b,d)->[(c,d) | c<-f b])

instance ArrowZero NonDet where zeroArrow = ND (\_->[])
instance ArrowPlus NonDet where ND f <+> ND g = ND (\a->f a ++ g a)
instance ArrowChoice NonDet where
    left (ND f) = ND (\i->case i of Left a ->then Left (f b)
                                    Right b->then Right [b])
instance ArrowApply NonDet where
    app = ND (\(ND f,a) -> f a)
```

Z M E N Y C H O V A N I

```
newtype MapTrans t a b = MT ((t->a) -> (t->b))

instance Arrow (MapTrans t) where
    arr f = ND (f .)
    MT f >>> MF g = MT (g . f)
    first (MT f) = MT (zipMap . (f`prod`id) . unzipMap) where
       zipMap  ::(t->a,t->b)->(t->(a,b))
       zipMap   (f,g) t = (f t, g t)
       unzipMap::(t->(a,b))->(t->a,t->b)
       unzipMap fg = (fst fg, snd fg)
--neni ArrowChoice ani ArrowApply
```

Funkcionální grafy

```
type Node = Int
class FGContext ctx where
  type FGVLabel ctx                                  type FGELabel ctx
  pre, suc :: ctx -> [(Node, FGELabel ctx)]          upre, usuc :: ctx -> [Node]
  ver :: ctx -> (Node, FGVLabel ctx)                 uver :: ctx -> Node

data FGView ctx gr = Missing gr | ctx :& gr
class FGraph gr where
  type FGCtx gr            empty :: gr                    isEmpty :: gr -> Bool
  nodes :: gr -> [(Node, FGVLabel (FGCtx gr)]             unodes :: gr -> [Node]
  edges :: gr -> [(Node, Node, FGELabel (FGCtx gr)]       uedges::gr->[(Node, Node)]
  using :: Node -> gr -> FGView (FGCtx gr) gr
  usingAny :: gr -> FGView (FGCtx gr) gr
  (&)::([FGEdge (FGCtx gr)], FGVertex (FGCtx gr), [FGEdge (FGCtx gr)])->gr->gr
  ...

dfs v g = dfs' [v] g where
 dfs' [v]     _                  = []
 dfs' (v:vs) (using v-> vc :& g ) = map ((,)v) (usuc vc) ++ dfs' (usuc vc++vs) g
 dfs' (v:vs) (using v->Missing g) = dfs' vs g

data SeqView a b = Empty | a :< b
class Seq a where
  type SeqElem a       empty :: a      isEmpty :: a -> Bool
  push :: SeqElem a -> a -> a          pop :: a -> SeqView (SeqElem a) a
  pushList xs s = foldl (flip push) s xs

dfs v g = dfs' (v `push` S.empty) g where
  dfs' (pop->Empty)  _                    = []
  dfs' (pop->v:<vs) (using v-> vc :& g ) =
                          map ((,)v) (usuc vc) ++ dfs' (pushList (usuc vc) vs) g
  dfs' (pop->v:<vs) (using v->Missing g) = dfs' vs g

bfs v g = bfs' (push v Q.empty) g where
  bfs' (pop->Empty)  _                    = []
  bfs' (pop->v:<vs) (using v-> vc :& g ) =
                          map ((,)v) (usuc vc) ++ bfs' (usuc vc `pushList` vs) g
  bfs' (pop->v:<vs) (using v->Missing g) = bfs' vs g

dijkstra v g = dij (push (0, v) H.empty) g where
  dij (pop->Empty)  _                     = FGraph.empty
  dij (pop->(d,v):<vs) (using v->Missing g) = dij vs g
  dij (pop->(d,v):<vs) (using v-> vc :& g ) =
         (pre vc, (v,d), suc vc) & dij (pushList [(d+w,s) | (s,w)<-suc vc] vs) g

prim (usingAny->Missing g) = FGraph.empty
prim (usingAny-> vc :& g ) =
 pri (add_succ 0 (uver vc) H.empty (suc vc)) g (([], ver vc, []) & FGraph.empty)
 where add_succ d v = foldr (\(s,w) -> push (d+w, s, (v, w)))
       pri (pop->Empty)          _                      st = st
       pri (pop->(d,v,p):<vs) (using v->Missing g) st = pri vs g st
       pri (pop->(d,v,p):<vs) (using v-> vc :& g ) st =
                         pri (add_succ d v vs (suc vc)) g (([p],ver vc,[]) & st)
```